IDEA-0929

Copy 12 of 12

22 October 1962

MEMORANDUM FOR: Chief, Operations Division, OSA-DD/R

SUBJECT : IDEALIST Logistics Support Requirements

- 1. The present KOD-IRAN program will be completed by 29 April 1963. This includes the conversion of two additional U-2A's to U-2F's. By that date, the project will have three U-2C's and five U-2F's for operational use. Except for the possible IRAN of Article 343 in the first quarter of 1964, all aircraft should remain in uninterrupted use until the 2nd and 3rd quarters of 1965. At that time a new IRAN cycle will begin.
- 2. With eight operational aircraft in the fleet as of 29 April 63, it is necessary to determine well in advance how they are to be distributed and what their programmed usage will be so that additional planning can be made for their logistic support.
- 3. At present, it appears there will be insufficient facilities, equipment, aircraft spares, engine spares,

 camera personnel, and funds to support an active operational and training program using all eight aircraft. In addition, the installation of and 25X1D in each aircraft will generate further support requirements which have not been programmed for. All of these factors must be re-examined in the light of an operational concept based on eight aircraft of which at least six will be operationally ready at any given time.
 - 4. An early decision is also required as to whether a second U-2 is to be assigned ______ This is only one facet of the over all distribution and usage problem mentioned above. However, if a second aircraft is assigned

25X1C

Approved For Release 2003/01/24 : CIA-RDP63-00313A000609100053-7-0-014

Approved For Release 2003/01/24 : CIA-ROP63-00313A000600100053-7

IDEA-0929 Page Two

25X1C	additional camera	will have 25X1D
	to be procured to replace 25X1D These are long lead-time items, so this action must be taken without delay.	
	5. It is realized that any operational concept which attempts to forecast numbers of detachments, flying hours, missions, and system requirements is subject to many variables, especially in the light of current developments. However, it is requested that the IDEALIST Concept of Operations dated 28 March 1962 be reviewed and that a meeting with key staff elements be held at the earliest possible time to re-program logistic support requirements for FY-63 and FY-64.	
	SIGNE	D'
		riel Division -DD/R
	Distribution: Cy 1 - Addee 2 - AD/OSA 3 - DAD/OSA 4 - C/DD/OSA 5 - COMMO/OSA 6 - CD/OSA 7 - ADMIN/OSA 8 - PB/OSA 9 - FIN/OSA 10 - SB/OSA 11 - MD/OSA	ΕV1 Λ
		5X1A

rme

MD/OSA-DD/R:

IDEA-0930 Copy 3

26 October 1962

The following is the UR information from Det. H for the month of September.

- 9-1 INDICATOR, TURN & BANK SP AN-5820T-3, S/N 4519. Pointer sets off center, width of half a paddle. Replaced with serviceable part S/N D5328.
- 9-2 INDICATOR, FREE AIR TEMP SP MS28009-1, S/N 4994. Erratic in operation. Replaced with serviceable part S/N 3785.
- 9-3 INDICATOR, ALTITUDE INTEGRAL STABILIZER 6610-663-880 (14602-1J-F1) S/N 41102. Inoperative in flight. Replaced with serviceable part S/N AF 56-41751.
- 9-4 TRANSMITTER, PPH FUEL FLOW SP 8TJ59GAT-3, S/N V-10048, 23:10 hrs. Erratic operation reported in flight. Replaced by serviceable part S/N S14701.
- 9-5 VALVE, FUEL TANK AIR REGULATOR SP 108136-16, S/N 116)-882, 290:05 hrs. Will not allow sufficient air for pressurizing fuel tanks. Replaced with serviceable part S/N 75P-370.
- 9-6 REGULATOR, A.C. VOLTAGE SP R329-7, S/N PY766, 99:40 hrs. Has been subjected to excessive heat along with alternator failure, Replaced with serviceable part S/N TY828.
- 9-7 ALTERNATOR, A.C. SP 329-3, S/N 329-3, S/N PYT71, 80:40 hrs. Reported failure in flight, beads of solder found in area of mounting on engine. Replaced with serviceable part S/N MW512.
- 9-8 VALVE, FUEL PILOT UPPER 2 on Assy. P/N SP 9-654-1, S/N 1206 and 1528, 290:05 hrs. Float sticks allowing fuel low level. warning light to come on in flight. Replaced with serviceable parts S/N 1224 and 1191.
- 9-9 VALVE, FUEL PILOT LOWER SP 9-654-1, S/N 290:05 hrs. Same as above. Replaced with serviceable part S/N 1347.
- 9-10 VALVE, FUEL SHUT-OFF 2 on Assy. SP 1321-556566, S/N
 161 and 286, 290:05 hrs. Same as above. Replaced with serviceable parkspylld 226Raleds 229Q3/01/24: CIA-RDP63-00313A000600100053-7

IDEA0930 Page 2

9-11 INDICATOR PPH. FUEL FLOW - SP 8DJ86IAA1, S/N S29424. Erratic and stick in operation. Replaced with serviceable part S/N S29414.

9-12 TRANSMITTER, FUEL COUNTER - SP-H-222, S/N 376114-M1, 36:15 hrs. Indication of sticking per flight report. Replaced by serviceable part S/N 376475-M1.

9-13 INDICATOR, TURN & BANK - SP AN-5820-T3, S/N D5328, 10:00 hrs. Indication of sticking per flight report. Replaced by serviceable part S/N 376475-M1.

9-14 INDICATOR, PPH FUEL FLOW - SP 8DJ86LAA1, S/N S29414, 15:05 hrs. Stuck for 20 minutes in flight. Replaced by serviceable part S/N T41966.

9-15 TRANSMITTER, FUEL COUNTER - SP H-222, S/N 376475-M1, 13:00 hrs. Stuck for 20 minutes in flight. Replaced with serviceable unit S/N 375348-M1.

9-16 EXHALATION VALVE, MEV-28A-137. Loss of tension in spring.

9917 HELMET BLADDER, S-692. Leak in faceplate contact.

9-18 HELMET BLADDER, S-692. Leak over right ear - puncture.

9-19 COUNTER, MP-10211. Two frequency counters received, both items inoperative. S/N 898 was shipped minus the very important Z201 subassembly. S/N 1030 could not be operated at all because of physical interference between the airfilter and the fan. This condition apparently was not caused by damage in shipment; rather it appears that the repair facility inserted a new filter prior to releasing item for shipment and the item was not properly bench-checked for proper operation.

9-20 Tracker Malfunction. Gear Train binding at altitude.

Sincerely

25X1A

DisApproved For Release 2003/01/24: CIA-RDP63-00313A000600100053-7

2 - MD/OSA 3 - RIB/OSA